

LFB Floodlights



Technical Datasheet



LFB-10NWC, LFB-20NWC & LFB-50NWC




These 10W, 20W and 50W IP65 LED based floodlights are capable of producing 800Lm, 1600Lm and 4000Lm respectively, are designed as replacements for traditional floodlights. The glass cover is 4mm strengthened clear glass which is fully waterproof and resistant to most environmental factors. The lighting source is made up of high power SMD LED's, which in turn are directly connected to the aluminium shell ensuring very low heat emissions and a much longer lifespan. They offer a natural light for improved visibility.

Features:

- EMC Approved
- IC Driver
- SMD LED
- Resistant to rust
- Slim aluminium casing

Applications

- Business
- Commercial
- Domestic

DESCRIPTION	LFB-10NWC	LFB-20NWC	LFB-50NWC
LED Power	10W	20W	50W
LED Type	SMD LED	SMD LED	SMD LED
Lumen Output	800Lm	1600Lm	4000Lm
Colour Temperature	4000K	4000K	4000K
Rated Life Hours	25 000 hours	25 000 hours	25 000 hours
Operating Voltage	175 - 250V	175 - 250V	175 - 250V
Frequency	50 - 60Hz	50 - 60Hz	50 - 60Hz
Power Factor	>0.5	>0.5	>0.9
CRI	>80	>80	>80
Beam Angle	110°	110°	110°
IP Grade	IP65	IP65	IP65
Weight	190g	265g	750g
Dimensions Width X Height X Depth (mm)	97 x 91.3 x 30.5mm 	128 x 104.5 x 30.5mm 	220 x 160 x 31mm 

Contact Us

Branches: Johannesburg | Cape Town | Durban | Port Elizabeth | Bloemfontein
011 872 5500 | 021 556 3091 | 031 569 1024 | 041 452 1172 | 051 430 4958
email: sales@major-tech.com www.major-tech.com

