



VETi
Microwave Sensors


The MS361 automatically turns on lights and creates automations. It detects through obstacles like doors, glass panels, and thin walls, with a 360° detection range and adjustable settings. Easily integrated into new or existing setups, it excels in detecting subtle movements over large areas compared to PIR sensors. Its IP20 rating limits it to indoor use, and installation must be done by a qualified professional.




Product Specification

Function	Range
Detection Area	
Ceiling Installation	360°
Wall Installation	180°
Detection Distance	
Ceiling Installation	2m - 16m (Adjustable)
Wall Installation	5m - 15m (Adjustable)
Detection Motion Speed	0.6 to 1.5m/s
HF System	5.8GHz CW Radar, ISM Band
Ambient Light	<3 to 2000 Lux (Adjustable)
Installation Height	
Ceiling Installation	2m to 8m
Wall Installation	5m to 15m
Voltage	220 to 240V AC
Power Frequency	50/60Hz
Rated Load	
Incandescent	1200W
LED / CFL	600W
Time Delay	10 sec (±3 sec) to 12 min (±1 min)
Power Consumption	<0.9W
Mounting	Ceiling & Wall Mount
Working Temperature	-20°C to 40°C
Working Humidity	<93% RH
IP Rating IP54	IP20 (Indoor Installation)
Standards	IEC 60669-1 / 60669-2-1 AS/NZS 60669.1 / 60669.2.1

Sensor Information




Ceiling Installation



Wall Installation



360° Detection Range



180° Detection Range

MS361 | **Microwave Motion Sensor**

Contact Us
South Africa

www.major-tech.com sales@major-tech.com

Australia

www.majortech.com.au info@majortech.com.au